



ASSOCIATION CONNECTING
ELECTRONICS INDUSTRIES

IPC-2615

Printed Board Dimensions and Tolerances

IPC-2615

July 2000

A standard developed by IPC

Table of Contents

1	PURPOSE	1	3	GEOMETRIC CHARACTERS AND SYMBOLS	3
1.1	Scope	1	3.1	General	3
1.2	General	1	3.2	Use of Notes to Supplement Symbols	3
1.2.1	Units	1	3.3	Symbol Construction	3
1.2.2	Reference to This Standard	1	3.3.1	Geometric Characteristic Symbols	3
1.2.3	Figures	1	3.3.2	Datum Feature Symbol	3
1.2.4	Notes	1	3.3.3	Basic Dimension Symbol	
1.2.5	Reference to Gauging	1	3.3.4	Material Condition Symbols	4
1.3	References	1	3.3.5	Diameter and Radius Symbols	4
1.3.1	IPC Specifications	1	3.3.6	Reference Symbol	4
1.3.2	ANSI Standards	1	3.4	Geometric Tolerance Symbols	4
2	TERMS AND DEFINITIONS	1	3.4.1	Feature Control Frame	4
2.1	Actual Size	1	3.4.2	Feature Control Frame Incorporating Datum References	4
2.2	Basic Dimension	1	3.4.3	Combined Feature Control Frame and Datum Feature Symbol	5
2.3	Bilateral Tolerance	1	3.5	Feature Control Frame Placement	6
2.4	Cumulative Tolerances	1	4	GENERAL RULES	7
2.5	Datum	2	4.1	Maximum Material Condition Principle (MMC) Effect of MMC	7
2.6	Datum Feature	2	4.2	Regardless of Feature Size	7
2.7	Datum Axis	2	4.3	Least Material Condition Principle	7
2.8	Datum Target	2	4.4	Limits of Size	7
2.9	Dependent of Size	2	4.4.1	Individual Feature of Size (Rule #1)	7
2.10	Dimension	2	4.4.2	Relationship Between Individual Features	9
2.11	End Product (End Item)	2	4.5	Applicability of MMC, RFS, and LMC	9
2.12	Fabrication Allowance	2	5	DATUM REFERENCING	9
2.13	Feature	2	5.1	General	9
2.14	Feature of Size	2	5.1.1	Application	9
2.15	Fiducial	2	5.1.2	Datum Reference Frame	10
2.16	Geometric Tolerance	2	5.2	Datum Features	10
2.17	Limits of Size	2	5.2.1	Datum Feature Symbols	10
2.18	Least Material Condition (LMC)	2	5.2.2	Datum Feature Control	10
2.19	Maximum Material Condition (MMC)	2	5.2.3	Specifying Datums in Order of Precedence	11
2.20	Positional Tolerance	2	5.3	Establishing Datums	12
2.21	Reference Dimension	2	5.3.1	Primary Datum Feature	12
2.22	Regardless of Feature Size (RFS)	2	5.3.2	Secondary and Tertiary Datum Features Not Subject to Size Variations	12
2.23	Simulated Datum	2	5.3.3	Secondary and Tertiary Datum Features Subject to Size Variations	12
2.24	Tolerance	2	5.3.4	Specifying Datum Features RFS	12
2.25	Tolerance, Statistical	2	5.3.5	Specifying Datum Features at MMC	13
2.26	Toleranced Dimension	3	5.3.6	Cylindrical Datum Features	13
2.27	True Position	3	5.3.7	Angular Orientation	16
2.28	Undimensioned Drawing	3			
2.29	Unilateral Tolerance	3			
2.30	Virtual Condition	3			

5.3.8 Pattern of Features to Establish a Secondary Datum 16

5.3.9 Multiple Datum Reference Frames 16

5.4 Datum Targets 18

5.4.1 Datum Target Symbols 18

5.4.2 Datum Target Dimensions 19

5.4.3 Datum Planes 19

6 TOLERANCES OF LOCATION 21

6.1 General 21

6.2 Positional Tolerancing 21

6.2.1 Feature Locations Given by Basic Dimensions 21

6.2.2 Feature Control Frame 21

6.2.3 Establish Datums for Dimensions Locating True Positions 21

6.2.4 Application to Base Line and Chain Dimensioning 21

6.3 Fundamental Explanation of Positional Tolerancing 21

6.3.1 Material Condition Basis 21

6.3.2 MMC as Related to Positional Tolerancing 21

6.3.3 LMC as Related to Positional Tolerancing 24

6.3.4 Multiple Patterns of Features Located by Basic Dimensions Relative to Common Datums 24

6.4 Feature Pattern Location 26

6.4.1 Composite Positional Tolerancing 26

6.5 Bi-directional Positional Tolerancing of Features 26

6.6 Position of Non-Circular Features 26

6.6.1 Non-circular Features at MMC 27

6.7 Undimensioned Drawings (Artwork) 27

7 TOLERANCES OF FORM, ORIENTATION, PROFILE 38

7.1 General 38

7.2 Form and Orientation Control 38

7.3 Specifying Form and Orientation Tolerances ... 38

7.3.1 Form and Orientation Tolerance Zones 38

7.4 Profile Control 38

7.4.1 Profile Tolerancing 39

7.4.2 Controlled Radius Tolerance 39

7.4.3 Angular Surfaces 39

Appendix A: FUNDAMENTAL DIMENSIONING AND TOLERANCING RULES 45

Appendix B: GENERAL TOLERANCING AND RELATED PRINCIPLES 56

Appendix C: DIMENSIONING FOR COMPUTER-AIDED DESIGN AND MANUFACTURING 58

Figures

Figure 3-1 Datum Feature Symbol 4

Figure 3-2 Examples of Datum Identification 5

Figure 3-3 Basic Dimension Symbol 5

Figure 3-4 Feature Control Frame 6

Figure 3-5 Feature Control Frame Incorporating Datum Report 6

Figure 3-6 Order of Precedence of Datum Reference 6

Figure 3-7 Multiple Feature Control Frames 7

Figure 3-8 Symbol for All Around 7

Figure 3-9 Combined Feature Control Frame and Datum Feature Symbol 7

Figure 3-10 Feature Control Frame Placement 7

Figure 4-1 Positional Tolerancing at MMC 8

Figure 4-2 Variations of Form Allowed By Size Tolerance 9

Figure 5-1 Datum Reference Frame 10

Figure 5-2 Datum Reference Frame to Printed Board Relationships 11

Figure 5-3 Datum Reference Using Printed Board Edges 12

Figure 5-4 Hole and Slot Establishing Secondary and Tertiary Datums 12

Figure 5-5 Additional Datum Example 13

Figure 5-6 Datum Feature Identification and Reference . 14

Figure 5-7 Secondary Datum Established By Internal Feature 14

Figure 5-8 Datum Feature and Simulated Datum 15

Figure 5-9 Virtual Condition of Datum Feature 15

Figure 5-10 Part With Cylindrical Datum Features (a) primary datum feature K, which establishes a datum plane; and (b) secondary datum feature M, which establishes a datum axis. 16

Figure 5-11 Cylindrical Internal Datum Features 17

Figure 5-12 Development of a Datum Reference Frame .. 17

Figure 5-13 Pattern of Feature to Establish Secondary Datum 18

Figure 5-14 Multiple Datum Reference Conditions (Rigid/Flex) Examples 18

Figure 5-15 Referencing Datums in Feature Control Frames 19

Figure 5-16 Datum Target Symbol 19

Figure 5-17 Datum Target Point 20

Figure 5-18 Dimensioning Datum Targets 20

Figure 5-19 Primary Datum Plane Established 21

Figure 6-1 Identifying Basic Dimensions 22

Figure 6-2 Positional Tolerances With Datum Reference 23

Figure 6-3 Positional Tolerancing 23

Figure 6-4 Establishing Datums for True Position Location 24

Figure 6-5 Basic Dimensioning Using Chain or Baseline Format 25

Figure 6-6 Boundary for Surface of Hole at MMC 26

Figure 6-7 Hole Axes in Relation to Positional Tolerance Zones 27

Figure 6-8 Increase in Positional Tolerance Where Hole is Not at MMC 28

Figure 6-9 Conventional Positional Tolerancing at MMC 29

Figure 6-10 Regardless of Feature Size Applied to A Feature and A Datum 29

Figure 6-11 Increase in Positional Tolerance Where Hole is not at LMC 30

Figure 6-12 LMC Applied to A Pattern of Mounting Pins ... 31

Figure 6-13 Multiple Patterns of Features 32

Figure 6-14 Tolerance Zones for Patterns Shown in Figure 6-13 33

Figure 6-15 Multiple Patterns of Features, Separate Requirement 34

Figure 6-16 Hole Patterns Located By Composite Positional Tolerancing 35

Figure 6-17 Tolerance Zone for Three-Hole Hole Patterns Shown in Figure 6-16. 36

Figure 6-18 Bi-Directional Positional Tolerancing, Rectangular Coordinate Method 37

Figure 6-19 Keying Slot Detail 37

Figure 6-20 "V" Groove 37

Figure 6-21 Keying Slot Detail 38

Figure 7-1 Application of A Profile of A Surface to A Contour 40

Figure 7-2 Specifying Profile of A Surface All Around 41

Figure 7-3 Specifying Different Profile Tolerance 42

Figure 7-4 Profile Implementation 42

Figure 7-5 Specifying A Controlled Radius 43

Figure 7-6 Tolerancing An Angular Surface Using A Combination of Linear and Angular Dimensions 43

Figure 7-7 Interpreting Angularity Tolerances 44

Figure 7-8 45 Degree Chamfer 44

Figure A-1 Angular Units 46

Figure A-2 Millimeter Dimensioning 46

Figure A-3 Decimal Inch Dimensioning 46

Figure A-4 Application of Dimensions 47

Figure A-5 Grouping of Dimensions 47

Figure A-6 Spacing of Dimensions 47

Figure A-7 Staggered Dimensions 47

Figure A-8 Dimension Line/Extension Line 47

Figure A-9 Oblique Extension Lines 48

Figure A-10 Breaks In Extension Lines 48

Figure A-11 Point Location 48

Figure A-12 Limited Length or Area Indication 48

Figure A-13 Leader-Directed Dimension 48

Figure A-14 Minimizing Leaders 49

Figure A-15 Leader Directed to Circle 49

Figure A-16 Reading Direction 49

Figure A-17 Intermediate Reference Dimension 49

Figure A-18 Radii 50

Figure A-19 Radius With Locating Center 50

Figure A-20 Radii With Unlocated Center 50

Figure A-21 Dimensioning Chords, Arcs, and Angles 50

Figure A-22 Fully Rounded Ends 51

Figure A-23 Partially Rounded Ends 51

Figure A-24 Rounded Corners 51

Figure A-25 Circular Arc Outline 51

Figure A-26 Coordinate or Offset Outline 51

Figure A-27 Tabulated Outline 51

Figure A-28 Round Holes 52

Figure A-29 Slotted Holes 52

Figure A-30 Equalized Chamfers 52

Figure A-31 Chamfers at Other Than 90°° 53

Figure A-32 Edge Card Connector 53

Figure A-33 Rectangular Coordinate Dimension 54

Figure A-34 Rectangular Coordinate Dimensions Without Dimension Lines 54

Figure A-35 Polar Coordinate Dimensions 54

Figure A-36 Repetitive Features and Dimensions 55

Figure A-37 Equal Spacing of Feature 55

Figure B-1 Limit Dimensions 56

Figure B-2 Plus or Minus Tolerances 57

Figure C-1 Mathematical Quadrants 58

Figure C-2 Locating A Circuit Pattern Using Fiducials Relative to Plated-Through Holes 59

Tables

Table 3-1 General Geometric Characteristic Symbols 3

Table 3-2 Special Application Symbols 3

Table 3-3 Modifying Symbols 6

Table 4-1 Maximum Material Condition Range 8

Table 4-2 Regardless of Feature Size Range 8

Table 4-3 Least Material Condition Range 9

Printed Board Dimensions and Tolerances

1 PURPOSE

The purpose of this Standard is to establish acceptable principals and practices for dimensioning and tolerancing used to define end-product requirements for printed boards and printed board assemblies.

1.1 Scope This Standard covers dimensioning and tolerancing of electronic packaging as it relates to printed boards and the assembly of printed boards. The concepts defined in this Standard are derived from ASME Y14.5M-1994. Printed boards have such wide applications that there may be times where this standard does not address a specific case. In those cases, the user is referred to ASME Y14.5M 1994 for use of additional dimensioning and tolerancing concepts.

1.2 General This Standard covers dimensioning, tolerancing, and related practices for use on printed board drawings and in related documents. Uniform practices for stating and interpreting these requirements are established herein.

1.2.1 Units The International System of Units (SI) is featured in this Standard.

1.2.2 Reference to This Standard Where drawings are based on this Standard, this fact shall be noted on the drawings or in a document referenced on the drawings. References to this Standard shall state "IPC-2615 or per IPC-2615."

1.2.3 Figures The figures in this Standard are intended only as illustrations to aid the user in understanding the principles and methods of dimensioning and tolerancing described in the text. The absence of a figure illustrating the desired application is neither reason to assume inapplicability nor basis for drawing rejection. In some instances figures show added detail for emphasis, in other instances figures are incomplete by intent. Numerical values of dimensions and tolerances are illustrative only.

1.2.4 Notes Notes herein in capital letters are intended to appear on finished drawings. Notes in lower case letters are explanatory only and are not intended to appear on drawings.

1.2.5 Reference to Gauging This document is not intended as a gauging standard. Any reference to gauging is included for explanatory purposes only.

1.3 References

1.3.1 IPC Specifications¹

IPC-T-50 Terms and Definitions

IPC-D-310 Guidelines for Phototool and Artwork Generation

IPC-D-325 Documentation for Printed Boards and Printed Board Assemblies

IPC-D-330 Design Guide for Printed Boards and Printed Board Assemblies

IPC-2220 Design Standard Series for Printed Boards

IPC-6010 Performance Specification Series for Printed Boards

1.3.2 ANSI Standards² When the following American National Standards referred to in this Standard are superseded by a revision approved by the American National Standards Institute, Inc., the latest revision shall apply.

ANSI Y14.1-1980, Drawing Sheet Size and Format

ANSI Y14.2M-1979, Line Conventions and Lettering

ASME Y14.5M-1994, Geometric Dimensioning and Tolerancing

ANSI Z210.1-1976, Metric Practice

2 TERMS AND DEFINITIONS

The definition of terms shall be in accordance with IPC-T-50 and the following.

2.1 Actual Size The measured size.

2.2 Basic Dimension A numerical value used to describe the theoretically exact size, profile, orientation, or location of a feature or datum target. It is the basis from which permissible variations are established by tolerances on other dimensions, in notes, or in feature control frames (see 3.4.1).

2.3 Bilateral Tolerance A tolerance in which variation is permitted in both directions from the specified dimension.

2.4 Cumulative Tolerances The summation of all tolerances permitted between functionally related features:

1. IPC, 2215 Sanders Road, Northbrook, IL 60062

2. ANSI, 655 15th Street N.W., Suite 300, Washington, DC 20005-5794